## **Atlas Lateral**



This information was last updated on 12 December 2023, is current as of that date and replaces all previous versions

## GAS SPECIFICATIONS AND PRESSURE REQUIREMENTS

The following is for indicative information only. The applicable specification is included in each gas transportation agreement, connection agreement or other agreement between Darling Downs Pipeline and its counterparties.

Component	Units	Min	Max
N <sub>2</sub>	mol%	0.00	3.50
CO <sub>2</sub>	mol%	0.00	1.50
Total Inert Gases	mol%	0.00	5.00
C1 (Methane)	mol%	94.00	100.00
C2 (Ethane)	mol%	0.00	0.15
C <sub>3+</sub> (Propanes +)	mol%	0.00	0.00
H <sub>2</sub> S	ppmv	0.00	4.00
Total Mercaptan Sulfur	ppmv	0.00	1.00
Carbonyl Sulphide	ppmv	0.00	2.00
Total Sulfur	mg/Sm <sup>3</sup>	0.00	20.00
Water Dew Point @ 13.5MPag	deg C	-	0.00
Hydrocarbon Dew Point @ 3.5 MPag	deg C	-	2.00
Oxygen	ppmv	0.00	10.00
Water	mg/Sm <sup>3</sup>	0.00	65.00
Mercury	μg/Sm³	0.00	20.00
Triethylene Glycol		Saturated	Saturated
BTEX	ppmv	0.00	4.00

Other: Reasonably free from dust, gum forming constituents, other liquids or solids. Reasonably free of unsaturated or aromatic hydrocarbons. Free of other substances that may cause damage to equipment or may form products that are hazardous to health.

Connection Point	Minimum Pressure (kPa)	Maximum Pressure (kPa)
DDP134	13,800	14,500